

# Compressed air tubing, Series TU1-S-PAM

- suitable for dynamic laying
- Ø 4 mm
- Polyamide
- Max. working pressure at 20 °C 15-26 bar



Max. working pressure at 20 °C  
Ambient temperature min./max.  
Weight

See table below  
-40 ... 80 °C  
0,006 kg

## Technical data

Part No.	external	Wall thickness	Color	Length	Bending radius min.
	-Ø			Delivery unit	At 20 °C
1820712100	4 mm	1 mm	Natural	25 m	20 mm
1820712110	4 mm	1 mm	Black	25 m	20 mm
R412009980	4 mm	0,5 mm	Silver gray	25 m	20 mm
R412009913	4 mm	0,5 mm	Blue	25 m	20 mm
R412009931	4 mm	0,5 mm	Black	50 m	20 mm
R412009937	4 mm	0,5 mm	Natural	50 m	20 mm
R412009914	4 mm	0,5 mm	Blue	100 m	20 mm
R412009943	4 mm	0,5 mm	Silver gray	100 m	20 mm

Part No.	Max. working pressure at 20 °C
1820712100	26 bar
1820712110	26 bar
R412009980	15 bar
R412009913	15 bar
R412009931	15 bar
R412009937	15 bar
R412009914	15 bar
R412009943	15 bar

price / m

## Technical information

- External calibrated
- Halogen-free
- Excellent hydrolysis characteristics
- Suitable for dynamic laying
- Excellent UV resistance
- Resistant to microbes

## Technical information

Material	
Material	Polyamide