



Test valve, MBV 5000

061B7000

Product name: Test Valve, Type: MBV 5000, Number of inputs [pc]: 1, Number of outputs [pc]: 1, Test function: Separate

Ambient temperature range [°C] [Max]	120 °C	Pressure Male/Female	Female
Ambient temperature range [°C] [Min]	-20 °C	Pressure range (Pi) [bar] [Max]	120 bar
Ambient temperature range [°F] [Max]	248 °F	Pressure range (Pi) [bar] [Min]	0 bar
Ambient temperature range [°F] [Min]	-4 °F	Pressure range (Pi) [bar] oil [Max]	180 bar
Approval	EAC RoHS LLC CDC EURO-TYSK	Pressure range (Pi) [bar] oil [Min]	0 bar
MiniMess included	Yes	Pressure thread conn standard	ISO 228-1
Number of inputs [pc]	1 pc	Product description	Test Valve
Number of outputs [pc]	1 pc	Product group	Shut-off and regulating valves
Operating temperature [°C] [Max]	120 °C	Product name	Test valve
Operating temperature [°C] [Min]	-20 °C	Pulse-snubber	No
Operating temperature [°F] [Max]	248 °F	Quantity per packing format	15 pc
Operating temperature [°F] [Min]	-4 °F	Specification key	MBV5000-1111
Output connection type	Flange	Test function	Separate
Packing format	Multi pack	Test pressure connection size	16 x 2
Pressure connection size	1/4	Test pressure connection type	M
Pressure connection standard	DIN 3852-E	Type	MBV 5000
Pressure connection type	G		